



Bearing No.	Boundary dimensions				Basic load ratings(kN)		Limiting speeds		Mass
	mm				Dynamic	Static	rpm		Kg
	d	D	B	r _{sm}	Cr	Cor	Grease	Oil	
23120	100	165	52	2	310	470	1,700	2,600	4.3
23120K	100	165	52	2	310	470	1,700	2,600	4.16
23120KW33C3	100	165	52	2	310	470	1,700	2,600	4.16
23120W33C3	100	165	52	2	310	470	1,700	2,600	4.3
23122	110	180	56	2	370	580	1,500	2,400	5.4
23122K	110	180	56	2	370	580	1,500	2,400	5.22
23122KW33C3	110	180	56	2	370	580	1,500	2,400	5.22
23122W33C3	110	180	56	2	370	580	1,500	2,400	5.4
23124	120	200	62	2	455	705	1,400	2,100	7.7
23124K	120	200	62	2	455	705	1,400	2,100	7.46
23124KW33C3	120	200	62	2	455	705	1,400	2,100	7.46
23124W33C3	120	200	62	2	455	705	1,400	2,100	7.7

23126	130	210	64	2	495	795	1,300	2,000	8.47
23126K	130	210	64	2	495	795	1,300	2,000	8.2
23126KW33C3	130	210	64	2	495	795	1,300	2,000	8.2
23126W33C3	130	210	64	2	495	795	1,300	2,000	8.47
23128	140	225	68	2.1	540	895	1,200	1,800	10.2
23128K	140	225	68	2.1	540	895	1,200	1,800	9.86
23128KW33C3	140	225	68	2.1	540	895	1,200	1,800	9.86
23128W33C3	140	225	68	2.1	540	895	1,200	1,800	10.2
23130	150	250	80	2.1	730	1,190	1,100	1,700	15.6
23130K	150	250	80	2.1	730	1,190	1,100	1,700	15.1
23130KW33C3	150	250	80	2.1	730	1,190	1,100	1,700	15.1
23130W33C3	150	250	80	2.1	730	1,190	1,100	1,700	15.6
23132	160	270	86	2.1	840	1,370	1,000	1,600	19.8
23132K	160	270	86	2.1	840	1,370	1,000	1,600	19.2
23132KW33C3	160	270	86	2.1	840	1,370	1,000	1,600	19.2
23132W33C3	160	270	86	2.1	840	1,370	1,000	1,600	19.8
23134	170	280	88	2.1	885	1,490	960	1,500	21.5
23134K	170	280	88	2.1	885	1,490	960	1,500	20.8
23134KW33C3	170	280	88	2.1	885	1,490	960	1,500	20.8
23134W33C3	170	280	88	2.1	885	1,490	960	1,500	21.5
23136	180	300	96	3	1,030	1,730	900	1,400	25.1
23136K	180	300	96	3	1,030	1,730	900	1,400	24.2
23136KW33C3	180	300	96	3	1,030	1,730	900	1,400	24.2
23136W33C3	180	300	96	3	1,030	1,730	900	1,400	25.1
23138	190	320	104	3	1,190	2,020	850	1,300	35.3
23138K	190	320	104	3	1,190	2,020	850	1,300	34.2
23138KW33C3	190	320	104	3	1,190	2,020	850	1,300	34.2
23138W33C3	190	320	104	3	1,190	2,020	850	1,300	35.3
23140	200	340	112	3	1,350	2,270	800	1,200	43.3
23140K	200	340	112	3	1,350	2,270	800	1,200	42
23140KW33C3	200	340	112	3	1,350	2,270	800	1,200	42
23140W33C3	200	340	112	3	1,350	2,270	800	1,200	43.3
23144	220	370	120	4	1,540	2,670	720	1,100	53.3
23144K	220	370	120	4	1,540	2,670	720	1,100	51.6
23144KW33C3	220	370	120	4	1,540	2,670	720	1,100	51.6

23144W33C3	220	370	120	4	1,540	2,670	720	1,100	53.3
23148	240	400	128	4	1,730	3,050	650	1,000	65.8
23148K	240	400	128	4	1,730	3,050	650	1,000	63.8
23148KW33C3	240	400	128	4	1,730	3,050	650	1,000	63.8
23148W33C3	240	400	128	4	1,730	3,050	650	1,000	65.8
23152	260	440	144	4	2,140	3,850	600	920	91.4
23152K	260	440	144	4	2,140	3,850	600	920	88.6
23152KW33C3	260	440	144	4	2,140	3,850	600	920	88.6
23152W33C3	260	440	144	4	2,140	3,850	600	920	91.4
23156	280	460	146	5	2,300	4,250	550	850	97.7
23156K	280	460	146	5	2,300	4,250	550	850	94.6
23156KW33C3	280	460	146	5	2,300	4,250	550	850	94.6
23156W33C3	280	460	146	5	2,300	4,250	550	850	97.7
23160	300	500	160	5	2,750	5,000	510	780	131
23160K	300	500	160	5	2,750	5,000	510	780	127
23160KW33C3	300	500	160	5	2,750	5,000	510	780	127
23160W33C3	300	500	160	5	2,750	5,000	510	780	131