



Bearing No.	Boundary dimensions				Basic load ratings(kN)		Limiting speeds		Mass
	mm				Dynamic	Static	rpm		Kg
	d	D	B	$r_{s \min}$	Cr	Cor	Grease	Oil	
23936	180	250	52	2	440	835	1,200	1,800	8.21
23936K	180	250	52	2	440	835	1,200	1,800	7.95
23936KW33C3	180	250	52	2	440	835	1,200	1,800	7.95
23936W33C3	180	250	52	2	440	835	1,200	1,800	8.21
23938	190	260	52	2	460	890	1,100	1,700	8.6
23938K	190	260	52	2	460	890	1,100	1,700	8.34
23938KW33C3	190	260	52	2	460	890	1,100	1,700	8.34
23938W33C3	190	260	52	2	460	890	1,100	1,700	8.6
23940	200	280	60	2.1	545	1,100	1,000	1,600	12.1
23940K	200	280	60	2.1	545	1,100	1,000	1,600	11.7
23940KW33C3	200	280	60	2.1	545	1,100	1,000	1,600	11.7
23940W33C3	200	280	60	2.1	545	1,100	1,000	1,600	12.1
23944	220	300	60	2.1	565	1,170	930	1,400	13.1

23944K	220	300	60	2.1	565	1,170	930	1,400	12.7
23944KW33C3	220	300	60	2.1	565	1,170	930	1,400	12.7
23944W33C3	220	300	60	2.1	565	1,170	930	1,400	13.1
23948	240	320	60	2.1	565	1,190	840	1,300	14
23948K	240	320	60	2.1	565	1,190	840	1,300	13.6
23948KW33C3	240	320	60	2.1	565	1,190	840	1,300	13.6
23948W33C3	240	320	60	2.1	565	1,190	840	1,300	14
23952	260	360	75	2.1	760	1,580	770	1,200	24
23952K	260	360	75	2.1	760	1,580	770	1,200	23.3
23952KW33C3	260	360	75	2.1	760	1,580	770	1,200	23.3
23952W33C3	260	360	75	2.1	760	1,580	770	1,200	24
23956	280	380	75	2.1	830	1,750	710	1,100	26.4
23956K	280	380	75	2.1	830	1,750	710	1,100	25.6
23956KW33C3	280	380	75	2.1	830	1,750	710	1,100	25.6
23956W33C3	280	380	75	2.1	830	1,750	710	1,100	26.4
23960	300	420	90	3	1,110	2,320	650	1,000	40
23960K	300	420	90	3	1,110	2,320	650	1,000	38.7
23960KW33C3	300	420	90	3	1,110	2,320	650	1,000	38.7
23960W33C3	300	420	90	3	1,110	2,320	650	1,000	40