



Bearing No.	Boundary dimensions				Basic load ratings(kN)		Limiting speeds		Mass
	mm				Dynamic	Static	rpm		Kg
	d	D	B	r _{smin}	Cr	Cor	Grease	Oil	
24122	110	180	69	2	450	755	1,500	2,400	7.07
24122K30	110	180	69	2	450	755	1,500	2,400	6.96
24122K30W33C3	110	180	69	2	450	755	1,500	2,400	6.96
24122W33C3	110	180	69	2	450	755	1,500	2,400	7.07
24124	120	200	80	2	575	945	1,400	2,100	10.3
24124K30	120	200	80	2	575	945	1,400	2,100	10.1
24124K30W33C3	120	200	80	2	575	945	1,400	2,100	10.1
24124W33C3	120	200	80	2	575	945	1,400	2,100	10.3
24126	130	210	80	2	585	995	1,300	2,000	11
24126K30	130	210	80	2	585	995	1,300	2,000	10.8
24126K30W33C3	130	210	80	2	585	995	1,300	2,000	10.8
24126W33C3	130	210	80	2	585	995	1,300	2,000	11
24128	140	225	85	2.1	670	1,150	1,200	1,800	13.3

24128K30	140	225	85	2.1	670	1,150	1,200	1,800	13.1
24128K30W33C3	140	225	85	2.1	670	1,150	1,200	1,800	13.1
24128W33C3	140	225	85	2.1	670	1,150	1,200	1,800	13.3
24130	150	250	100	2.1	885	1,520	1,100	1,700	20.2
24130K30	150	250	100	2.1	885	1,520	1,100	1,700	20
24130K30W33C3	150	250	100	2.1	885	1,520	1,100	1,700	20
24130W33C3	150	250	100	2.1	885	1,520	1,100	1,700	20.2
24132	160	270	109	2.1	1,040	1,780	1,000	1,600	26
24132K30	160	270	109	2.1	1,040	1,780	1,000	1,600	25.6
24132K30W33C3	160	270	109	2.1	1,040	1,780	1,000	1,600	25.6
24132W33C3	160	270	109	2.1	1,040	1,780	1,000	1,600	26
24134	170	280	109	2.1	1,080	1,880	960	1,500	27.2
24134K30	170	280	109	2.1	1,080	1,880	960	1,500	26.8
24134K30W33C3	170	280	109	2.1	1,080	1,880	960	1,500	26.8
24134W33C3	170	280	109	2.1	1,080	1,880	960	1,500	27.2
24136	180	300	118	3	1,250	2,210	900	1,400	34.3
24136K30	180	300	118	3	1,250	2,210	900	1,400	33.8
24136K30W33C3	180	300	118	3	1,250	2,210	900	1,400	33.8
24136W33C3	180	300	118	3	1,250	2,210	900	1,400	34.3
24138	190	320	128	3	1,420	2,480	850	1,300	42.8
24138K30	190	320	128	3	1,420	2,480	850	1,300	42.2
24138K30W33C3	190	320	128	3	1,420	2,480	850	1,300	42.2
24138W33C3	190	320	128	3	1,420	2,480	850	1,300	42.8
24140	200	340	140	3	1,630	2,900	800	1,200	53.4
24140K30	200	340	140	3	1,630	2,900	800	1,200	52.6
24140K30W33C3	200	340	140	3	1,630	2,900	800	1,200	52.6
24140W33C3	200	340	140	3	1,630	2,900	800	1,200	53.4
24144	220	370	150	4	1,880	3,400	720	1,100	67
24144K30	220	370	150	4	1,880	3,400	720	1,100	66
24144K30W33C3	220	370	150	4	1,880	3,400	720	1,100	66
24144W33C3	220	370	150	4	1,880	3,400	720	1,100	67
24148	240	400	160	4	2,110	3,800	650	1,000	82.2
24148K30	240	400	160	4	2,110	3,800	650	1,000	80.9
24148K30W33C3	240	400	160	4	2,110	3,800	650	1,000	80.9
24148W33C3	240	400	160	4	2,110	3,800	650	1,000	82.2

24152	260	440	180	4	2,510	4,600	600	920	114
24152K30	260	440	180	4	2,510	4,600	600	920	112
24152K30W33C3	260	440	180	4	2,510	4,600	600	920	112
24152W33C3	260	440	180	4	2,510	4,600	600	920	114
24156	280	460	180	5	2,730	5,200	550	850	120
24156K30	280	460	180	5	2,730	5,200	550	850	118
24156K30W33C3	280	460	180	5	2,730	5,200	550	850	118
24156W33C3	280	460	180	5	2,730	5,200	550	850	120
24160	300	500	200	5	3,300	6,400	510	780	161
24160K30	300	500	200	5	3,300	6,400	510	780	159
24160K30W33C3	300	500	200	5	3,300	6,400	510	780	159
24160W33C3	300	500	200	5	3,300	6,400	510	780	161